

Ref. OPREA 150M



15,0" CCTV & Surveillance Desktop LCD-TFT Monitor with VESA Mount & CVBS input through BNC Connector



*Designed
for CCTV and
Surveillance applications*



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules
08551 - Tona - BARCELONA
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24
www.soltec-ep.com

DISPLAY

Panel Technology	Edge LED
Display Area (mm)	304.13(H) x 228.10(V)
Size	15"
Pixel Pitch (mm)	0,297 x 0,297
Screen Aspect	4:3
Native Resolution	1024 x 768
Viewing Angle LRUD	70°/70°/60°/60°
Contrast ratio	700:1 (Typ)
Brightness cd/m2	250 (Typ)
Colors	16,7M Colours
Response Time	30ms Ton +Toff
Life Time (hours)	35.000

CONNECTIVITY

Analogue RGB input	1xDB15
Composite CVBS Input	1xBNC
S-Video Input	1xMiniDIN
Video System	PAL, SECAM, NTSC
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

AUDIO

Speakers	2x2W
Audio IN	RCA, Audio R+Audio L
Headphone	1 x jack Stereo

ELECTRICAL

Power Supply Input	90/260VAC 50~60Hz
Power Supply Adaptor	12VDC / 4A
LCD Consumption	20W
Energy Management	VESA DPMS

DIMENSIONS (mm)

VESA Mount	75x75
With Base (WxHxD)	386,5x343,5x182,7
Without Base (WxHxD)	386,5x318,1x67,4
Weight Net /Gross	4Kg / 5Kg
Packing (WxHxD)	419x380x142

ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	10 to 90
Storage Humidity (%)	10 to 90

OTHERS

Certification	FCC; CE; RoHS
Plug & Play	VESA DDC/CI, DDC2B
OSD Menu	Multi-Languages
Accessories	220VAC Power Cord User Manual

OPTIONS

Touch Screen	Capacitive Technology
--------------	-----------------------

Specifications subject to changes without previous notice