

Ref. SKCV190M-28



SXGA 19" Professional Kiosk with Curved design Housing



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules
08551 - Tona - BARCELONA
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24
www.soltec-ep.com

DISPLAY

Panel Technology	Edge LED Technology
Display Area (mm)	376.3(H) x 301.06(V)
Size	19.0"
Pixel Pitch (mm)	0,294 x 0,294
Screen Aspect	5:4
Native Resolution	1280 x 1024
Viewing Angle LRUD	85°/85°/80°/80°
Contrast ratio	1000:1 (Typ)
Brightness cd/m2	350 (Typ)
Colors	16,7 M Colors
Response Time	5ms Ton +Toff
Life Time (hours)	50.000
Touch Screen	Capacitive Technology

BUILT-IN PC

CPU	ATOM D2550 1.86GHz
Chipset	Intel PCH NM10
RAM Memory	2x1GB DDR3 SO-DIMM
HDD	250GB SATA
Ethernet chipset	Intel 82583V Gigabit
Graphics Chipset	Intel GMA 3600

ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
Power Consumption	45W
Energy Management	VESA DPMS

DIMENSIONS (mm)

Net without base	1552x500x75
Net with base	1552x600x350

Net Weight (Kg)	60
Packing	1620x770x540

ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	5 to 90
Storage Humidity (%)	5 to 90

OTHERS

Security	CE; RoHS
Accessories	220VAC Power Cord Installation Manual

OPTIONS

Industrial Computer	Intel i5 3,2GHz RAM 4GB DDR3
Webcam	HD 720p
Amplifier + Speakers	2W x 2W Speakers
Protective Glass	4mm tempered glass
keyboard+trackball	Stainless steel IP65
High Brightness Panel	1.600cd/m2
Thermal Printer	60/80/120/A4
Bar Code Reader	Lineal, PDF417, QR
Magnetic Band Reader	Manual / Motorized
RFID Reader	reader/reader+writer
Customized Housing	
Option 1	Painted RAL Palette
Option 2	Stainless steal housing
Option 3	Outdoor IP65

Specifications subject to changes without previous notice