

Ref. SKSK170M-28



17" SXGA Interactive Kiosk with classic and slim design



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules
08551 - Tona - BARCELONA
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24
www.soltec-ep.com

DISPLAY

Panel Technology	Edge LED
Display Area (mm)	337,92(H) x 270,33(V)
Size	17,0"
Pixel Pitch (mm)	0,264 x 0,264
Screen Aspect	5:4
Native Resolution	1280 x 1024
Viewing Angle UDLR	80°/80°/85°/85°
Contrast ratio	800:1 (Typ)
Brightness cd/m2	350 (Typ)
Colors	16,7 M Colors
Response Time	30ms Ton +Toff
Life Time (hours)	50.000
Touch Screen	Capacitive Technology

BUILT-IN PC

CPU	ATOM D2550 1.86GHz
Chipset	Intel PCH NM10
RAM Memory	2x1GB DDR3 SO-DIMM
HDD	250GB SATA
Ethernet chipset	Intel 82583V Gigabit
Graphics Chipset	Intel GMA 3600

ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
Power Consumption	45W
Energy Management	VESA DPMS

DIMENSIONS (mm)

Net without base	1200x400x50
Net with base	1200x475x375

Packing (WxHxD)	1280x580x530
Net Weight (Kg)	60

ENVIRONMENTAL CONDITIONS

Operation Temperature	-30° to 85°
Storage Temperature	-30° to 85°
Operation Humidity (%)	8 to 90
Storage Humidity (%)	8 to 90

OTHERS

Security	CE; RoHS
Plug & Play	VESA DDC2Bi
Accessories	220VAC Power Cord Installation Manual

OPTIONS

Industrial Computer	Intel i5 3,2GHz RAM 4GB DDR3
Amplifier + Speakers	2W x 2W Speakers
Protective Glass	4mm tempered glass
keyboard+trackball	Stainless steel IP65
High Brightness Panel	1.600cd/m2
Thermal Printer	60/80/120/A4
Bar Code Reader	Lineal, PDF417, QR
Magnetic Band Reader	Manual / Motorized
RFID Reader	reader/reader+writer
Customized Housing	Option 1 Painted RAL Palette Option 2 Stainless steal housing Option 3 Outdoor IP65

Specifications subject to changes without previous notice