

Ref. SKSK215M-28



## 21.5" Full HD Interactive Kiosk with classic and slim design



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules  
08551 - Tona - BARCELONA  
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24  
[www.soltec-ep.com](http://www.soltec-ep.com)

### DISPLAY

Panel Technology	S-PVA Technology
Display Area (mm)	475.2(H) x 267.3(V)
Size	21.5"
Pixel Pitch (mm)	0,248 x 0,248
Screen Aspect	16:9
Native Resolution	1.920 x 1.080
Viewing Angle UDLR	88°/88°/88°/88°
Contrast ratio	5000:1 (Typ)
Brightness cd/m2	300 (Typ)
Colors	16,7 M Colors
Response Time	16ms Ton +Toff
Life Time (hours)	50.000
Touch Screen	Capacitive Technology

### BUILT-IN PC

CPU	ATOM D2550 1.86GHz
Chipset	Intel PCH NM10
RAM Memory	2x1GB DDR3 SO-DIMM
HDD	250GB SATA
Ethernet chipset	Intel 82583V Gigabit
Graphics Chipset	Intel GMA 3600

### ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
Power Consumption	45W
Energy Management	VESA DPMS

### DIMENSIONS (mm)

Net without base	1200x550x50
Net with base	1200x595x350

Packing (WxHxD)	1280x650x530
Net Weight (Kg)	60

### ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	5 to 90
Storage Humidity (%)	5 to 90

### OTHERS

Security	CE; RoHS
Plug & Play	VESA DDC2Bi
Accessories	220VAC Power Cord Installation Manual

### OPTIONS

Industrial Computer	Intel i5 3,2GHz RAM 4GB DDR3
Amplifier + Speakers	2W x 2W Speakers
Protective Glass	4mm tempered glass
keyboard+trackball	Stainless steel IP65
High Brightness Panel	1.200cd/m2
Thermal Printer	60/80/120/A4
Bar Code Reader	Lineal, PDF417, QR
Magnetic Band Reader	Manual / Motorized
RFID Reader	reader/reader+writer
Customized Housing	<b>Option 1</b> Painted RAL Palette <b>Option 2</b> Stainless steal housing <b>Option 3</b> Outdoor IP65

Specifications subject to changes without previous notice