

SMUP850M-10

DATA SHEET

MUP M Line



MUP M Line · Digital Signage

Our most exclusive Digital Multimedia Totem line with a housing made of painted steel with rounded sides.



SMUP850M-10

SOLTEC TECHNICAL SPECIFICATIONS

DIGITAL SIGNAGE

MUP M Line

GENERAL DESCRIPTION

Digital Multimedia Totem with 85" Professional TFT panel Built-in. Housing made of painted steel with rounded sides from our MUP-M Line. Designed to be fixed to the floor internally with no visible screws. It can be painted at any RAL Colour. Available with a full range of options detailed in the next page.

Full range of options available.



DISPLAY

Panel Technology	S-PVA Edge LED
Display Area (mm)	1872.0 (H) x 1053.0 (V)
Size	85"
Pixel Pitch (mm)	0.4875 x 0.4875
Screen Aspect	16:9
Native Resolution	3.940 x 2.160
Viewing Angle UDLR	89°/89°/89°/89°
Contrast Ratio	4000:1 (Typ)
Brightness cd/m2	700 (Typ)
Colors	1.07 B Colors
Response Time	8.5 ms Ton + Toff
Life Time (hours)	60.000

CONNECTIVITY

Analogue RGB Input	1xDB15
Digital Input	1xDVI-D 1xDP
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

ELECTRICAL

Power Supply Input	110/120VAC 50-60Hz
Power consumption for the standad reference	190W
Energy Management	VESA DPMS

MECHANICAL (SMUP850M-10)

Net (mm)	TBD
Base (Optional)	TBD
Packing (WxHxD)	TBD
Net Weight (Kg)	TBD

ENVIRONMENTAL CONDITIONS

Operation Temperature	-5° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	10 to 90
Storage Humidity (%)	10 to 90

OTHERS

Certifications	CE; RoHS
Plug & Play	VESA DDC2Bi
Accessories	Mains Power Cord User Manual

ORDERING INFORMATION

SMUP850M-10	Standard 85.0" MUP-M Line
SMUP850M-18	85.0" MUP-M Line with built-in PC Intel J3455 Quardcore CPU RAM 4GB DDR3 Intel HD Graphics Chipset
SMUP850M-15	85.0" MUP-M Line with built-in DMP Digital Media Player

Specifications subject to change without prior notice

SMUP850M-10

SOLTEC
STANDARD AVAILABLE OPTIONS

DIGITAL SIGNAGE


MUP M Line

85.0" Professional Digital Multimedia Totem

Built-in PC



High Brightness



Touch Screen




Protective glass



Speakers



Housing Customization



ORDERING INFORMATION OPTIONS

I3 - CPU

Intel i3 CPU upgrade

I5 - CPU

Intel i5 CPU upgrade

I7 - CPU

Intel i7 CPU upgrade

8RAM

8GB RAM DDR3 upgrade

16RAM

16GB RAM DDR3 upgrade

32RAM

32GB RAM DDR3 upgrade

PCT850DP

85.0" Projected Capacitive Touch Screen (Outdoor)

PCT850IN

85.0" Projected Capacitive Touch Screen

IR-850-X

85.0" Infrared Technology (X=2/6/12/32) simultaneous touches

850HB

2500cd/m² High Brightness TFT with High Tni 110° option

G850L

85.0" 6mm Laminated Protective Glass

G850AG

85.0" 6mm Anti-Glare Laminated Protective Glass

RALxxxx

Customized RAL Color

CUSTOM

Customized housing as per customer requirements



Specifications subject to change without prior notice

