

Ref. SARM320T-10



## SunReadable Full HD 32" Transflective Professional Monitor VESA Mount Housing with TFT surface Cooling System



*Designed  
for Windows-Shop and  
Digital Signage applications*



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules  
08551 - Tona - BARCELONA  
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24  
[www.soltec-ep.com](http://www.soltec-ep.com)

### DISPLAY

Panel Technology	Edge LED Technology
Display Area (mm)	698.4(H) x 392.8(V)
Size	31,5"
Pixel Pitch (mm)	0,363 x 0,363
Screen Aspect	16:9
Native Resolution	1.920 x 1.080
Viewing Angle UDLR	89°/89°/89°/89°
Contrast ratio	3000:1 (Typ)
Brightness cd/m2	Indoor 500 (Typ) Outdoor 1.400 80Klux
Colors	16.7M Colors
Response Time	6,5ms Ton +Toff
Life Time (hours)	50.000

### CONNECTIVITY

Analogue RGB input	1xDB15
Digital Input	1xDVI
Display Port	DP 1.1a
Plug & Play	VESA DDC2Bi
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

### ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
LCD Consumption	75W
Energy Management	VESA DPMS

### DIMENSIONS (mm)

VESA Mount	200x200
Net (WxHxD)	830x610x100
Net Weight (Kg)	23
Packing (WxHxD)	930x650x250

### ENVIRONMENTAL CONDITIONS

Operation Temperature	+0° to 50°
Storage Temperature	-20° to 65°
Operation Humidity (%)	10 to 90
Storage Humidity (%)	10 to 90

### OTHERS

Sensors	Light + Temperature
Security	CE; RoHS
Accessories	220VAC Power Cord Installation Manual

### OPTIONS

Industrial Computer	
Option 1	ATOM D2550 1,86GHz RAM 2GB DDR3
Option 2	Intel i5 3,2GHz RAM 4GB DDR3
Digital Media Player	Full HD Built-in Player
Remote Control	IR receiver + batteries
Customized Color	Landscape or Portrait RAL Palette

Specifications subject to changes without previous notice