

ZINIA420ARM12

DATA SHEET

ZINIA ARM Line



ZINIA ARM Line · Ultra-wide TFT Monitor

Ultra-wide Professional TFT Monitor design to be installed with any standard VESA bracket



ZINIA420ARM12

SOLTEC
TECHNICAL SPECIFICATIONS


ULTRA-WIDE TFT MONITOR

ZINIA ARM Line

GENERAL DESCRIPTION

Ultra-wide Professional TFT Monitor designed to be installed with any standard VESA bracket. Available as a basic monitor, with a built-in PC and with a built-in digital media player.

High Brightness



Protective glass



PC Integrated



Full HD Panel



Full range of options available.



DISPLAY

Panel Technology	Edge LED Technology
Display Area (mm)	930.2 (H) x 243.2 (V)
Size	37.6"
Pixel Pitch (mm)	0.478 x 0.478
Screen Aspect	16:4.5
Native Resolution	1920 x 540
Viewing Angle UDLR	178°/178°
Contrast Ratio	8000:1 (Typ)
Brightness cd/m2	1.000 (Typ)
Colors	16.7 M Colors
Response Time	9.5ms Ton + Toff
Life Time (hours)	100.000

CONNECTIVITY

VGA Input	1xDB15
Digital Input	1xDVI
Plug & Play	VESA DDCBi
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

ELECTRICAL

Power Supply Input	110/220VAC 50-60Hz
LCD Consumption	50W
Energy Management	VESA DPMS

MECHANICAL (ZINIA420ARM12)

VESA Mount	400x200
Net (WxHxD)	1010x323x100
Net Weight	12
Packing	1110x423x200

ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	10 to 90
Storage Humidity (%)	10 to 90

OTHERS

Certifications	CE; RoHS
Accessories	Mains Power Cord User Manual

OPTIONS

Industrial Computer	
Option 1	ATOM D2550 1.85GHz RAM 2GB DDR3
Option 2	Intel i5 3.2GHz RAM 4GB DDR3
Digital Media Player	Full HD Built-in Player
Protective Glass	6mm Laminated glass

Specifications subject to change without prior notice

